

# t4000

## Through The Wall Solution



# ATM

The **Hantle t4000** ATM provides an economical, high performance through-the-wall solution. Designed and built with compact **modular** components and engineered for **easy installation**.

The t4000 offers a host of high-end features including a **10.4" Sun-Viewable Color LCD** supporting custom screen advertisements and communication via **56K Modem** or integrated **Ethernet (SSL)**.

The t4000 is **TDES** and **ADA** compliant out of the box, including a **PCI/VISA/Interac certified encrypting PIN pad (EPP)**, a voice guidance system, and lighted action indicators.

**HANTLE**

“Tomorrow’s Technology for Today’s Market”

# t4000

**HANTLE**  
www.hantle.com

## INTEGRATED ILLUMINATED TOPPER

Integrated illuminated topper for creating high visibility and attracting customers

## HIGH-BRIGHT MONITOR

10.4 inch diagonal 32-bit color, backlit Sun-viewable TFT LCD panel  
800 x 600 SVGA resolution

## ADA

Accessible keypad layout  
Voice guidance  
Lighted action indicators



## PRINTER

3 1/8" Thermal receipt printer.  
Can print custom graphic

## CARD READER

Manual insert (dip) magnetic card reader  
EMV (optional)

## KEYPAD

16-key alphanumeric keypad  
VISA/Interac PCI certified  
Triple DES (TDES) compliant  
Encrypting PIN pad (EPP)

## CPU

Cortex-A8 CPU (800MHz)  
DDR2 256MB SRAM memory  
512MB Flash Memory  
Windows CE 6.0

## COMMUNICATION

56K dial-up modem or Ethernet (TCP/IP)  
On-board SSL Encryption

## REAR SERVICE PANEL

Perform Operator Tasks and Diagnostics

## CASH DISPENSER

Sliding cash dispensing unit for easy service  
2,000 note removable cassette



## SECURITY

UL 291 Business Hour listed  
Electronic lock  
Cencon Lock (optional)

## ADVANCED SERVICES

The Hantle t4000 comes with a steel pedestal which can be adjusted from 25" to 35". The pedestal carries the entire weight of the machine so you can install the t4000 in thin walls or facades.

## SPECIFICATIONS

### Dimensions

33" H 24" W 28" D

Weight : 319 lbs

\* optional dispensers will increase overall weight

### Operating Environment:

Temperature range: 40°F-95°F

Relative humidity: Non-condensing - 15%-85%

### Options and Upgrades:

Cencon Electronic Lock

EMV Card Reader